



Eco-Screen™ Toilet Compartment System Technical Specifications

Partition Core Material

LEED supporting paper composite panels using post consumer recycled paper that is FSC certified, virgin fibers which have been approved by the SmartWood and the Rainforest Alliance and /or eucalyptus fibers which are rapidly renewable.

Nominal thickness

3/4" panels and doors, 3/4" pilasters

Colors Available

Colors Available from FSC certified recycled paper: Evergreen, Slate, Gun Metal, Sienna, Mocha, Chocolate, Denim, Cabernet, R50 and R100

Colors Available from FSC certified virgin fiber and Eucalyptus fibers: Leather, Black Diamond, Redstone, Green Mountain, Yellow Island, Chocolate Glacier, and Blue Canyon

System Components

Wall Panel(s)
Pilaster(s)
Door(s)
Head rail(s)
Urinal Screen(s)

HARDWARE COMPONENTS

Note: Hardware configuration and application may vary depending upon system design. Clarification provided in shop drawing schematics after field dimension verification.

Wall Panel

Two (2) 3/4" full-length aluminum U-channel.
Stainless steel tamper proof through bolts for mounting U-channel to panel.

Pilaster/Door

Two (2) cast stainless steel pivot hinges per door / pilaster.

*Left-hand in-swing / out-swing and right-hand in-swing / out-swing must be specified.

One (1) stamped stainless steel surface mounted latch-slide per door.

One (1) stamped stainless steel surface mounted strike & keeper per pilaster.

1/4" - 20 stainless steel tamper proof screws used for any exposed hardware mounting.

One (1) steel mounting foot per pilaster.

One (1) stainless 3" high pilaster shoe per pilaster.

Head Rail

Extruded Aluminum

Urinal Screen

(1) Two-ear 3/4" aluminum U-channel.